

P650

VACUUM CHAMBER MACHINE



MULTIVAC

BETTER PACKAGING



SWING-LID, DOUBLE-CHAMBER VACUUM MACHINE

FEATURING:

- Stainless steel housing, feet and lid.
- Free-standing unit
- Automatic progressive ventilation.
- Double-seam separation sealing.
- Function for vacuum quick-stop.
- Three program memory spaces.
- Chamber size: 33.5" x 33.5".
- Lid Height: 9.8" (interior height).
- Overall Dimensions: 84.64"l x 45.27"w (61.02"h when open)
- Heavy-duty, locking casters.
- Twelve month warranty.

DISTRIBUTED EXCLUSIVELY BY



Processor Division

55710 NW 41ST STREET • RIVERSIDE MO 64150
800-456-5624 • www.bunzlpdpackaging.com

P650

VACUUM CHAMBER MACHINE



Stainless Steel Swing lid.

Lid swings down on one side for cycling, while the other side can be unloaded and reloaded.



Double-seam separation sealing.

P650 seals with a three mm wide primary seal seam and a one mm wide separation seam. The excess film on the pouch can be easily pulled off at the separation seam without using a tool. Also available with gas flushing unit.



Automatic progressive ventilation

When products with sharp edges are being packed, such as pork chops, kebab skewers or salmon portions, the pouch wraps itself gently around the contours of the packed product, reducing the risk of puncturing the pouch.



Filling plates

Filling plates reduce the volume of the chamber, when smaller or flat products are being packed. The smaller the remaining volume, the shorter the required evacuation time.



Three memory spaces for user programs

The evacuation and sealing times for frequently used applications can be saved on three keys. This includes the gas flushing time in the case of machines with a gas flushing unit.



MULTIVAC Hygienic Design™

Flat deck design for easy cleaning and disinfection with fluids. Easy-care materials and smooth surfaces ensure quick and simple cleaning. Filling plates, insert and plug-in sealing bar easily removable without tools.



Electric

220V/3P/60Hz/40A

Cord length: 16.4' pigtail cord.

Compressed Air

Max. input pressure – 7.0 bar, Min. input pressure – 1.0 bar. Sealing pressure – 1.0 bar.

SPECIFICATIONS

ITEM NO.	DESCRIPTION	SEAL BAR LENGTH	CYCLE PER MINUTE	PUMP	ELECTRICAL VOLTS/PHASE/HERTZ/AMPS	GAS	AIR	CASTERS
B529 0001	P650	33.5" x 4 bars	2-3	10.0 HP	220V3P60HZ40A	Y	Y	Y

DISTRIBUTED EXCLUSIVELY BY



Processor Division

5710 NW 41ST STREET • RIVERSIDE MO 64150
800-456-5624 • www.bunzlpdpackaging.com